

Edge 1055



Product Snapshot

Proxim's Edge 1055 is a versatile small wireless broadband solution that provides reliable communication in noisy environments.

Offering the same multi-use versatility as the Edge 1025, the Edge 1055 provides the added flexibility of operation in the 4.9 GHz and 5 GHz bands. It also supports 5, 10, 20, and 40 MHz channel sizes where spectrum is limited.

- Wide Band 4.9 and 5 GHz Radio
- 2x2 MIMO radio delivering up to 294 Mbps
- Advanced QoS for quad-play applications
- AES 128 encryption and Radius authentication
- 5, 10, 20, and 40 MHz channels.

One Device, Multiple Uses

Whether you need a Point-to-Point endpoint, Multipoint CPE, or MultiPoint Base Station, the Edge 1055 does it all.

Powered by WORP[®]

Proxim WORP enables the most efficient wireless broadband access possible in a packet-based network.

Advanced QoS controls, committed interface rates, latency controls, IGMP snooping, and native multicast support allow granular service level management and the best video performance available in this product class.

Flexible Antenna Options

Includes an integrated 15 dBi 35-degree dual-polarity antenna and offers external connectors for extended range.

Secure

AES 128 encryption with Radius-based authentication and secure management through SSL/ TLS1.2, SSH, and SNMPv3.

Rugged Reliability

IP67 rated metal enclosure to ensure years of reliable service in harsh environments, including high winds, high salt, and temperature extremes.

Specifications

PRODUCT MODELS

MP-1055-BS3-WD	Edge Multipoint 1055, Base Station, integrated antenna and RP-SMA	PN: 901-00335
MP-1055-BS3-32SU-UPG	Edge Multipoint 1055, Base Station, support for 1 to 32 SU license upgrad	PN: 997-00060

INTERFACES

WIRED ETHERNET	One auto MDI-X RJ45 10/100/1000Mbps Ethernet with PoE in
WIRELESS PROTOCOL	WORP® (Wireless Outdoor Router Protocol)

RADIO & TX SPECS

MIMO	2x2
MODULATION	OFDM BPSK-QAM256
FREQUENCY	4.900 – 5.925 GHz (Subject to Country Regulations)
CHANNEL SIZE	5, 10, 20 and 40 MHz
TX POWER	Up to 24 dBm (dual chain)
TX POWER CONTROL	0 - 21 dB, in 1 dB steps. Automatic TPC with configurable EIRP limit

	5 MHz	10 MHz	20 MHz	40 MHz
TX POWER	MCS0:	MCS0:	MCS0:	MCS0:
2 RF	23	24	24	23
	MCS7:	MCS7:	MCS8:	MCS9:
2 RF	20	20	19	18
RX SENSITIVITY (Per=10 ⁻⁶)	MCS0:	MCS0:	MCS0:	MCS0:
	-95	-92	-89	-86
	MCS7:	MCS7:	MCS8:	MCS9:
	-78	-75	-67	-62
Throughput-MIMO 2x2 Mode	25 Mbps	50 Mbps	122 Mbps	294 Mbps
OTHER	Dynamic Channel Selection (DCS) based on interference detection, Dynamic Frequency Selection (DFS) based on radar signature			
	Automatic Transmit Power Control (ATPC) with EIRP limit support			

MANAGEMENT

REMOTE	Telnet and SSH, Web GUI and SSL/TLS1.2, TFTP, SNMPv3
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB
OTHER	Syslog, sFlow™ agent, SNTP and local time, Spectrum analyzer
Multi-Language Support	Web Interface available in English, French, Spanish and Chinese


SECURITY

ENCRYPTION	AES 128
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication (with VLAN and QoS provisioning)

ANTENNA

Integrated 2x2 MIMO 15 dBi (12 dBi below 5 GHz) Dual Polarized 35 degree Panel Antenna plus two RP-SMA Connectors
(Software switch between integrated antenna and connectors)

ANTENNA PATTERNS (Sector Mode)



QoS

Asymmetric Bandwidth Control	Asymmetric UL/DL committed and maximum information rate per service flow
Packet Classification Capabilities	802.1p priority, IPTOS, VLAN ID, IP addresses, ports, Ethernet addresses, IP protocol, and EtherType
Scheduling	Best Effort, Real Time Polling Services

NETWORK

MODES	Bridging, Routing (RIP v2 and IP tunneling)
IP STACK	IPv4 and IPv6 simultaneously
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs, PPPoE end point with Proxy DNS
VLAN	802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging

POWER

802.3af/at compliant

POWER CONSUMPTION

10 W typical, 12 W max in MIMO 2x2 mode

ENVIRONMENTAL SPECS	OPERATING TEMPERATURE	STORAGE TEMPERATURE	HUMIDITY - IP RATING	WIND LOADING
	-30° to 55° Celsius (-22° to 131° Fahrenheit) Temporary increases up to 60°C (140° Fahrenheit) will not impact operation of the unit.	-50° to 70° Celsius (-58° to 158° Fahrenheit)	100% relative humidity– IP67	180 km/h (112.5 mph)
PHYSICAL SPECS	DIMENSIONS PACKAGED	DIMENSIONS UNPACKAGED	WEIGHT (PACKAGED)	WEIGHT (UNPACKAGED)
MP-1055-BS3	310 x 226 x 98 mm (12.2 x 8.9 x 3.85 in)	170 x 217 x 56 mm (6.7 x 8.55 x 2.2 in)	2.15 kg (4.74 lbs)	1.19 kg (2.62 lbs)

SAFETY STANDARDS

IEC 62368-1:2014 & 60950-22:2016
CAN/CSA C22.2 No 62368-1:14 & No 60950-22:17
EN 62368-1:2014 + A11:2017 & 60950-22:2017

CERTIFICATIONS

USA FCC part 15B class B (EMC), part 15E (5.2 and 5.8 GHz radio) and part 90Y (4.9 GHz radio)
EUROPE EN 301 489-1 + EN 301 489-17

PACKAGE CONTENTS

- One Edge MP-1055-BS3 with integrated antenna plus two RP-SMA connectors
- Two SMA weather proofing caps
- One M25 weather proofing cable gland
- One wall mounted power injector with US to EU plug adapter
- One pair of hose clamps
- One Grounding kit
- One Quick Installation Guide

MTBF & WARRANTY

>250 000 hours, 2-year warranty, ServPak Extended Support available.

ABOUT PROXIM WIRELESS :

Proxim Wireless is a global leader in advanced wireless broadband and WiFi solutions that deliver high performance and high availability communications.

Celebrating 40 years of pioneering wireless solutions, Proxim is recognized for unparalleled reliability, superior performance, and drive for innovation.

© 2022 Proxim Wireless Corporation. All rights reserved. Proxim is a registered trademark and the Proxim logo is a trademark of Proxim Wireless Corporation. All other trademarks mentioned herein are property of their respective owners. Specifications are subject to change without notice.