



## Edge Quickbridge 1035 - a cost effective wireless backhaul solution

The Proxim Edge Quickbridge 1035 is a highly reliable outdoor, high throughput Point to Point system designed to deliver years of reliable service and priced to fit cost-sensitive medium-range backhaul projects.

The Edge Quickbridge 1035 enables rapid deployment of fast and efficient networks and offers:

- High throughput MIMO 2x2:2 with radio rates of 400 Mbps at 40 MHz (license upgradable to 866 Mbps at 80 MHz)<sup>1</sup>.
- High power radio delivering up to 24 dBm (2 RF) at 5 GHz.
- High reliability and advanced QoS for quad play applications.
- Dual IPv4 and IPv6 stacks.
- IP67 rated enclosure with surged protected ethernet port.

The Edge Quickbridge is powered by Proxim's advanced Wireless Outdoor Router Protocol (WORP). Among the many benefits of WORP is its effective use of bandwidth, granular service level management, and an advanced Quality of Service engine.

### Highly Secure

The Edge Quickbridge 1035 provides enterprise-class security to ensure full protection of sensitive information.

- AES 128 encryption and Radius based authentication.
- Secure management (SSL/TLS1.2, SSH, and SNMPv3).

### Easy to Deploy

The Edge Quickbridge 1035 simplifies network deployment and includes:

- Link kit: two endpoints in a box.
- Built-in 15 dBi 30-degree dual-polarity antenna, plus RP-SMA connectors for external antennas when an extended range is needed.
- Hose clamps for pole mounting .
- 802.3af/at Power over Ethernet.
- Bluetooth Low Energy interface for easy configuration via the Proxim BlueConnect smartphone application for Android and iOS.

### Centralized Management

The Edge Quickbridge 1035 is fully integrated into the ProximVision<sup>®</sup> Advanced management platform, giving network operators advanced management and monitoring options including:

- Rapid Network Deployment: automates configuration processes for faster, more efficient deployment of Proxim Wireless networks.
- Advanced Statistic and Analytic data for network optimization.

### Key Technologies

#### Proxim WORP<sup>®</sup>

Combines network access control, data scheduling, advanced QoS and encryption to ensure highly efficient and secure data transmission.

#### Proxim ClearConnect<sup>™</sup>

A suite of interference mitigation technologies ensuring robust and reliable communications in high-density wireless deployments.

### About Proxim Wireless

Proxim Wireless is a pioneer and global leader in advanced Wi-Fi, point to point, and point to multipoint outdoor wireless systems that deliver high performance and high availability communications.

With over 30 years of wireless experience, Proxim is recognized for its unparalleled reliability, superior performance and drive for innovation.

<sup>1</sup> A license upgrade to activate 80MHz will be available in a future software release.

## Specifications

PRODUCT MODELS		PART NUMBERS	
QB-1035-LNK	Edge Quickbridge 1035, link, 400 Mbps, integrated antenna and RP-SMA (Two QB-1035-EPR)	902-00907 QB-1035-LNK-WD	
INTERFACES			
WIRED ETHERNET WIRELESS PROTOCOL	One auto MDI-X RJ45 10/100/1000Mbps Ethernet with PoE in WORP® (Wireless Outdoor Router Protocol)		
RADIO & TX SPECS			
MIMO MODULATION FREQUENCY CHANNEL SIZE DATA RATE TX POWER TX POWER CONTROL	2x2:2 OFDM BPSK-QAM256 5.150 – 5.925 GHz (Subject to Country Regulations) 20 and 40 MHz (license upgrade to 80 MHz) Up to 400 Mbps (license upgrade upto 866 Mbps) Up to 24 dBm (dual chain) 0 - 17 dB, in 1 dB steps. Automatic TPC with configurable EIRP limit		
			<b>Requires License Upgrade</b>
	<b>20 MHz</b>	<b>40 MHz</b>	<b>80 MHz</b>
TX POWER	MCS0:	MCS0:	MCS0:
2 RF	24	24	23
	MCS8:	MCS9:	MCS9:
2 RF	20	20	19
RX SENSITIVITY (Per=10 <sup>-6</sup> )	MCS0:	MCS0:	MCS0:
	-94	-91	-88
	MCS8:	MCS9:	MCS9:
	-71	-66	-62
OTHER	Dynamic Channel Selection (DCS) based on interference detection, Dynamic Frequency Selection (DFS) based on radar signature Automatic Transmit Power Control (ATPC) with EIRP limit support		
ANTENNA			
	Integrated 2x2 MIMO 15 dBi Dual Polarized 30 degree Pannel Antenna plus two RP-SMA Connectors (Software switch between integrated antenna and connectors)		
MANAGEMENT			
REMOTE	Telnet and SSH, Web GUI and SSL/TLS1.2, TFTP, SNMPv3		
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB		
OTHER	Syslog, sFlow™ agent, SNTP and local time, Spectrum analyzer		
Multi-Language Support	Web Interface available in English, French, Spanish and Chinese		
SECURITY			
ENCRYPTION	AES 128		
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication (with VLAN and QoS provisioning)		
QoS			
Asymmetric Bandwidth Control	Asymmetric UL/DL committed and maximum information rate per service flow		
Packet Classification Capabilities	802.1p priority, IPTOS, VLAN ID, IP addresses, ports, Ethernet addresses, IP protocol, and EtherType		
Scheduling	Best Effort, Real Time Polling Services		
NETWORK			
MODES	Bridging, Routing (RIP v2 and IP tunneling)		
IP STACK	IPv4 and IPv6 simultaneously		
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs, PPPoE end point with Proxy DNS		
VLAN	802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging		
POWER			
	802.3af/at compliant		

POWER CONSUMPTION				
	10 W			
ENVIRONMENTAL SPECS	OPERATING TEMPERATURE	STORAGE TEMPERATURE	HUMIDITY - IP RATING	WIND LOADING
	-30° to 55° Celsius (-22° to 131° Fahrenheit)	-50° to 70° Celsius (-58° to 158° Fahrenheit)	100% relative humidity – IP67	180 km/h (112.5 mph)
PHYSICAL SPECS	DIMENSIONS PACKAGED	DIMENSIONS UNPACKAGED	WEIGHT (PACKAGED)	WEIGHT (UNPACKAGED)
QB-1035-EPR	310 x 226 x 98 mm (12.2 x 8.9 x 3.85 in)	170 x 217 x 56 mm (6.7 x 8.55 x 2.2 in)		1.24 kg (2.73 lbs)
SAFETY STANDARDS				
	UL/IEC/EN 62386-1 and 60950-22			
PACKAGE CONTENTS				
	<ul style="list-style-type: none"> <li>• One Edge Quickbridge QB-1035-LNK with integrated antenna plus two RP-SMA connectors (Two QB-1035-EPR)</li> <li>• Four RP-SMA weather proofing caps</li> <li>• Two M25 weather proofing cable glands</li> <li>• Two power injectors and country specific power cords</li> <li>• Two pair of hose clamps</li> <li>• Two Grounding kits</li> <li>• Two Quick Installation Guides</li> </ul>			
MTBF & WARRANTY				
	>250 000 hours, 2-year warranty, ServPak Extended Support available.			