

3.3-3.8 GHz Dual Slant WiMAX Base Station Antenna, 65°

-MA-WC35-DS17

MARS Dual Slant Base Station Antenna is light-weight yet has a robust and durable construction.

Additional Features:

- specially designed for WiMAX applications
- quick and easy installation
- easy mounting allows to obtain required downtilt
- suitable for harsh environment installations
- DC grounded

Applications:

- WiMAX - licensed band applications
- Point-to-Multi Point Applications
- WLL applications



Specifications:

Electrical

Frequency range	3.3 - 3.8 GHz
Gain,typ.	16.5 dBi
VSWR, max.	1.7:1
3 dB Beam-Width, H-Plane, typ.	65 °
3 dB Beam-Width, E-Plane, typ.	8 ° Down tilt : 2°
Polarization	Dual Polarized $\hat{A}\pm 45\text{deg}$
Port to Port Isolation	- 30 dB
Front to Back Ratio	-25 dB
Input power, max	50 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	600 x 225 x 40 mm (23.6â€•x8.9â€•x1.6â€•)
Weight	1.8 kg
Connector	2 x N-Type, Female (bottom)
Back Plane	Aluminum protected through chemical passivation
Radome	UV Protected Plastic
Mount	<u>MNT-22</u>

Environmental

Operating Temperature Range	- 40°C to + 65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Ice and Snow	25mm radial (survival)
Salt Fog	According to IEC 68-2-11
Service Life	>10 years

Standard Compliance

ETSI EN 302 085 V1.2.3 â€“ CS1

Ordering Options

Antenna with mount	MA-WC35-DS17 B
--------------------	----------------

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product and are available in the "Policies" section.