

4.9-6.1 GHz Dual Slant Base Station Antenna, 60°

- MA-WC55-DS17

MARS Dual Slant ± 45 degrees 60° sector antenna features:

- efficient and stable performance with 17 dBi of gain
- Full 4.9-6.1 GHz band coverage
- High Isolation ratio
- Compact size
- Optional Azimuth & Elevation Adjustable mount
- UV protected radome suitable for harsh environment installations
- Square shape



Specifications:

Electrical

Frequency range	4.9 - 6.1 GHz
Gain, typ.	17 dBi
VSWR, max.	1.7:1
3 dB Beam-Width, H-Plane, typ.	60 °
3 dB Beam-Width, E-Plane, typ.	8 °
Polarization	Dual Slant ± 45°
Port to Port Isolation	- 35 dB
Front to Back Ratio	-30 dB
Input power, max	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x14.5" x1.6")
Weight	1.8 kg
Connector	2x N-Type, Female
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected, Plastic
Mount	<u>MNT-22</u>

Environmental

Operating Temperature Range	- 40°C to + 65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Ice and Snow	25mm radial (survival)
Salt Fog	According to IEC 68-2-11

Ordering Options

Antenna with mount	MA-WC55-DS17 B
--------------------	----------------

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product and are available in the "Policies" section.