



4.9-6.1 GHz Dual Polarized Base Station Antenna, $60\hat{A}^{o}$

- MA-WC56-DP17

Specifications:

MARS $60 \hat{A}^o$ Broadband Dual Polarized Sector Antenna provides a cost effective solution for large scale WLL, WLAN, H-LAN, ISM, UNII, Public Safety, Municipal MESH Networks and Point-to-Multi-Point applications. Additional Features:

- stable performance with 17 dBi of gain
- compact size allowing for easy blending with any environment
- tilt mount allowing for quick and easy installation
- UV protected radome suitable for harsh environment installations



Frequency range	4.9 - 6.1 GHz
Gain,typ.	18 dBi @ V-pol, 17 dBi@ H-pol
VSWR, max.	1.7:1
3 dB Beam-Width, H-Plane, typ.	60 °
3 dB Beam-Width, E-Plane, typ.	8°
Side Lobes, min.	V-pol - ETSI EN 302 085 V1.2.3 – CS2 , H-pol - ETSI EN 302 085 V1.2.3 – C
Polarization	Dual, Vertical and Horizontal
Cross Polarization, min.	-16 dB
Port to Port Isolation	- 40 dB
Front to Back Ratio, min.	-30 dB
Input power, max	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded
Mechanical	·
Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x14.5" x1.6")
Weight	1.8 kg
Connector	2 x N-Type, Female
Back Plane	Aluminum protected through chemical passivation
Radome	UV Protected, Plastic
Mount	MNT-22
Environmemtal	
Operating Temperature Range	- 55°C to + 65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Ice and Snow	25mm radial (survival)
Salt Fog	According to IEC 68-2-11
Service Life	>10 years
Ordering Options	

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product and are available in the $\hat{a} \in \infty$ Policies $\hat{$