

MA-WC90-DS13

850-960 MHz Dual Slant Base Station Sector Antenna, 65°

MARS 915 MHz Dual Slant Base Station Sector Antenna provides a robust and efficient solution for the Point-to-Multipoint systems based on the ISM 915 MHz band.

Additional Features:

- 65° azimuthally coverage.
- Suitable for harsh environment installations.
- DC grounded.



Specifications

Electrical

Frequency range	850-960 MHz
GAIN, typ.	13 dBi
VSWR, max.	1.7 : 1
Polarization	Dual Slant ±45°
3 dB Beam-Width, Azimuth Plane, typ.	65°
3 dB Beam-Width, Elevation Plane, typ.	19°
Side Lobes, typ.	-12 dB
Cross Polarization, typ.	-15 dB
Port to Port Isolation, min.	-24 dB
Front to Back Ratio, typ.	-26 dB
Input power, max	20 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	960 x 330 x 120 mm
Weight	4 kg.
Connector	2 X N-Type
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Plastic
Mount	MNT-25

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Specifications

MA-WC90-DS13	Antenna Suited for MNT-25 (optional tilt mount)
MA-WC90-DS13B	Antenna with MNT-25 mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com