

5 GHz Dual Polarized Antenna ideal for Tsunami 8100 subscriber unit

Features

- Efficient and stable performance
- High gain/size ratio
- Light weight and durable construction
- UV protected radome made of polycarbonate allowing for harsh weather installations
- Easy mounting allowing for Azimuth and Elevation adjustment
- Dual Polarity (H/V) or dual slant (+/- 45°) installation



| Technical Specifications | | | |
|--------------------------------|--|-----------------------------|--|
| ELECTRICAL | | MECHANICAL | |
| FREQUENCY RANGE | 4.9 - 5.875 GHz | DIMENSIONS (HXWXD) | 370 x 370 x 40 mm (14.5" x14.5" x1.6") |
| GAIN | 23.5 dBi | WEIGHT | 2.1 kg |
| VSWR, MAX. | 1.7:1 | CONNECTOR | 2 x N-Type, Female |
| 3 DB BEAM-WIDTH, H-PLANE, TYP. | 8 ° | BACK PLANE | Aluminum; protected through chemical passivation |
| 3 DB BEAM-WIDTH, E-PLANE, TYP. | 8° | RADOME | UV Protected Polycarbonate |
| SIDE LOBES, MIN. | ETSI TS3, TS4, TS5 | MOUNT | MNT-22 |
| POLARIZATION | Linear, Vertical and Horizontal Can be mounted in dual slant mode | ENVIRONMENTAL | |
| CROSS POLARIZATION, TYP. | -25 dB | OPERATING TEMPERATURE RANGE | -40° C to +65° C |
| PORT TO PORT ISOLATION | - 30 dB | VIBRATION | According to IEC 60721-3-4 |
| FRONT TO BACK RATIO, MIN. | ETSI TS3, TS4, TS5 | WIND LOAD | 200 km/h (survival) |
| INPUT POWER, MAX | 5 Watt | FLAMMABILITY | UL94 |
| INPUT IMPEDANCE | 50 Ohm | WATER PROOFING | IP-67 |
| LIGHTNING PROTECTION | DC Grounded | HUMIDITY | ETS 300 019-1-4, EN 302 085 (annex. A.1.1) |
| | | SALT FOG | According to IEC 68-2-11 |
| | | SERVICE LIFE | > 10 years |

